



CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 7/7/2025 Version: 1.0

SECTION 1: Identification

1.1. Identification

Trade name : CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz
Product code : 1004977
Part number : 14424

1.2. Recommended use and restrictions on use

Recommended use : Stainless-steel cleaner
Restrictions on use : This product is not compliant to be sold for use in New York.

1.3. Supplier

Manufactured or sold by:

CRC Industries, Inc.
885 Louis Dr.
Warminster, PA 18974
United States
T 1-800-556-5074
crcindustries.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300
24-Hour Emergency

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

| | |
|---|--|
| Aerosol, Category 3 | Pressurized container: may burst if heated. |
| Skin corrosion/irritation, Category 2 | Causes skin irritation. |
| Serious eye damage/eye irritation, Category 2A | Causes serious eye irritation. |
| Aspiration hazard, Category 1 | May be fatal if swallowed and enters airways. |
| Hazardous to the aquatic environment — Acute Hazard, Category 3 | Harmful to aquatic life. |
| Hazardous to the aquatic environment — Chronic Hazard, Category 3 | Harmful to aquatic life with long lasting effects. |

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Pressurized container: may burst if heated
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation

Precautionary statements (GHS US) :

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not pierce or burn, even after use.

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Wear protective gloves, eye and face protection.

Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area.

Wash hands thoroughly after handling.

If swallowed: Immediately call a poison center or doctor.

Do NOT induce vomiting.

If on skin: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice or attention.

Take off contaminated clothing and wash it before reuse.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Chemical name / Synonyms | Product identifier | % |
|--|---|---------------------|---------|
| Water | Water | CAS-No.: 7732-18-5 | 45 - 70 |
| White mineral oil (petroleum) | White mineral oil (petroleum) | CAS-No.: 8042-47-5 | 10 - 30 |
| Distillates (petroleum), hydrotreated light | Distillates (petroleum), hydrotreated light | CAS-No.: 64742-47-8 | 5 - 10 |
| Petroleum gases, liquefied, sweetened | Petroleum gases, liquefied, sweetened | CAS-No.: 68476-86-8 | 5 - 10 |
| Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) | Sulfobutanedioic acid 1,4-bis(2-ethylhexyl)ester sodium salt dioctyl sodium sulfosuccinate | CAS-No.: 577-11-7 | 1 - 3 |

Comments : Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| | |
|---------------------------------------|--|
| First-aid measures after skin contact | : Take off contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Do not induce vomiting. Call a physician immediately. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |

4.2. Most important symptoms and effects (acute and delayed)

| | |
|-------------------------------------|---|
| Symptoms/effects after inhalation | : Prolonged inhalation may be harmful. |
| Symptoms/effects after skin contact | : Causes skin irritation. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. |
| Symptoms/effects after ingestion | : Aspiration may cause pulmonary edema and pneumonitis. |

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Specific hazards arising from the chemical

| | |
|--|--|
| Fire hazard | : Pressurized container: may burst if heated. |
| Explosion hazard | : Explosion risk in case of fire. Pressurized container may rupture when exposed to heat or flame. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

5.3. Special protective equipment and precautions for fire-fighters

| | |
|--------------------------------|--|
| Precautionary measures fire | : Keep container tightly closed and away from heat, sparks and flame. |
| Firefighting instructions | : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|---|
| General measures | : Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters. |
|------------------|---|

6.1.1. For non-emergency personnel

| | |
|----------------------|--|
| Protective equipment | : Wear recommended personal protective equipment. |
| Emergency procedures | : Ventilate spillage area. Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Avoid contact with skin and eyes. |

6.1.2. For emergency responders

| | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Evacuate unnecessary personnel. Stop leak if safe to do so. |

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak, if possible without risk. Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination. Notify authorities if product enters sewers or public waters.
- Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wear personal protective equipment. Avoid contact with skin and eyes. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Pressurized container: Do not pierce or burn, even after use. Exposure to high temperature may cause can to burst. Do not use if spray button is missing or defective. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product usage instructions, see the product label.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Level 1 Aerosol. Store locked up. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum gases, liquefied, sweetened (68476-86-8)

USA - ACGIH - Occupational Exposure Limits

| | |
|----------------------|----------------------------------|
| Local name | Butane |
| ACGIH® TLV® STEL | 1000 ppm (EX - Explosion hazard) |
| Remark (ACGIH) | TLV® Basis: CNS impair |
| Regulatory reference | ACGIH 2024 |

USA - OSHA - Occupational Exposure Limits

| | |
|------------|---------|
| Local name | Propane |
|------------|---------|

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| Petroleum gases, liquefied, sweetened (68476-86-8) | |
|---|--------------------------|
| OSHA PEL TWA | 1800 mg/m ³ |
| | 1000 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| White mineral oil (petroleum) (8042-47-5) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH® TLV® STEL | 10 mg/m ³ |
| USA - OSHA - Occupational Exposure Limits | |
| OSHA PEL C | 5 mg/m ³ |

| White mineral oil (petroleum) (8042-47-5) | |
|--|----------------------------------|
| Occupational Exposure Limit | 5 mg/mg ³ TLV (ACGIH) |

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

| |
|--|
| Hand protection: |
| Wear protective gloves such as: Nitrile, Polyvinylchloride (PVC) |
| Eye protection: |
| Wear safety glasses with side shields (or goggles). |
| Skin and body protection: |
| Wear appropriate chemical resistant clothing. |
| Respiratory protection: |
| If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Milky white
Odor : Mild petroleum.
Odor threshold : No data available
Melting point : -56.2 °F (-49 °C) estimated
Freezing point : -56.2 °F (-49 °C) estimated
Boiling point : 200 °F (93.3 °C) estimated
Flammability (solid, gas) : Not applicable.
Explosion limits : No data available

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| | |
|---|---|
| Flash point | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| pH | : 10.5 |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Solubility | : Water: Soluble |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Vapor pressure | : No data available |
| Evaporation rate | : Slow |
| Density and/or relative density | |
| Density | : 7.673 lb/gal Concentrate |
| Relative density | : 0.92 Concentrate |
| Relative vapor density at 20°C | : No data available |
| Particle characteristics | : No data available |
| Explosive properties | : Pressurized container: may burst if heated. |
| Oxidizing properties | : No data available |

9.2. Additional Regulatory Information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Pressurized container: may burst if heated. Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-------------------------------------|---|
| Symptoms/effects after inhalation | : Prolonged inhalation may be harmful. |
| Symptoms/effects after skin contact | : Causes skin irritation. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. |
| Symptoms/effects after ingestion | : Aspiration may cause pulmonary edema and pneumonitis. |
| Acute toxicity (oral) | : Not classified (Based on available data, the classification criteria are not met) |
| Acute toxicity (dermal) | : Not classified (Based on available data, the classification criteria are not met) |
| Acute toxicity (inhalation) | : Not classified (Based on available data, the classification criteria are not met) |

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| | |
|--|---|
| Petroleum gases, liquefied, sweetened (68476-86-8) | |
| LC50 Inhalation - Rat (Dust/Mist) | 658 mg/l Source: IUCLID |
| Distillates (petroleum), hydrotreated light (64742-47-8) | |
| LD50 oral rat | > 15000 mg/kg Source: IUCLID |
| LD50 dermal rabbit | > 2000 mg/kg Source: IUCLID |
| LC50 Inhalation - Rat | > 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 - |
| LC50 Inhalation - Rat (Dust/Mist) | > 5.2 mg/l Source: IUCLID |
| Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) (577-11-7) | |
| LD50 oral rat | 1900 mg/kg Source: Corporate Solution From Thomson Micromedex |
| LD50 oral | 4620 mg/kg body weight |
| LD50 dermal rabbit | 10000 mg/kg Source: International Uniform Chemical Information Database |
| LC50 Inhalation - Rat (Dust/Mist) | 20000 mg/l |
| White mineral oil (petroleum) (8042-47-5) | |
| LD50 oral rat | > 5000 mg/kg Source: International Uniform Chemical Information Database |
| LD50 dermal rabbit | > 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LC50 Inhalation - Rat | > 5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity) |
| Skin corrosion/irritation | : Causes skin irritation. pH: 10.5 |
| Serious eye damage/irritation | : Causes serious eye irritation. pH: 10.5 |
| Water (7732-18-5) | |
| pH | 7 |
| Respiratory or skin sensitization | : Not classified (Based on available data, the classification criteria are not met) |
| Germ cell mutagenicity | : Not classified (Based on available data, the classification criteria are not met). |
| Carcinogenicity | : Not classified (Based on available data, the classification criteria are not met). |
| Reproductive toxicity | : Not classified (Based on available data, the classification criteria are not met) |
| Distillates (petroleum), hydrotreated light (64742-47-8) | |
| NOAEL (animal/male, F0/P) | ≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)] |
| STOT-single exposure | : Not classified (Based on available data, the classification criteria are not met) |
| STOT-repeated exposure | : Not classified (Based on available data, the classification criteria are not met) |
| Petroleum gases, liquefied, sweetened (68476-86-8) | |
| LOAEC (inhalation, rat, gas, 90 days) | 12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other: |
| Distillates (petroleum), hydrotreated light (64742-47-8) | |
| NOAEL (oral, rat, 90 days) | 750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| NOAEL (dermal, rat/rabbit, 90 days) | ≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) |

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) (577-11-7) | |
|--|--|
| NOAEL (oral,rat,90 days) | > 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| White mineral oil (petroleum) (8042-47-5) | |
| NOAEL (oral,rat,90 days) | ≥ 1200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |
| Aspiration hazard | : May be fatal if swallowed and enters airways. |
| Viscosity, kinematic | : No data available |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

| Distillates (petroleum), hydrotreated light (64742-47-8) | |
|--|---|
| LC50 - Fish [1] | 2.4 mg/l Source: ECOTOX |
| Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) (577-11-7) | |
| LC50 - Fish [1] | 28 mg/l Source: International Uniform Chemical Information Database |
| EC50 - Crustacea [1] | 36 mg/l Source: International Uniform Chemical Information Database |
| EC50 - Other aquatic organisms [1] | 36 mg/l waterflea |
| White mineral oil (petroleum) (8042-47-5) | |
| LC50 - Fish [1] | > 10000 mg/l Source: IUCLID |

12.2. Persistence and degradability

| CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz | |
|--|--|
| Persistence and degradability | No data is available on the degradability of this product. |

12.3. Bioaccumulative potential

| Water (7732-18-5) | |
|--|---|
| Partition coefficient n-octanol/water (Log Pow) | -1.38 |
| Petroleum gases, liquefied, sweetened (68476-86-8) | |
| Partition coefficient n-octanol/water (Log Pow) | ≤ 2.8 Source: IUCLID |
| Distillates (petroleum), hydrotreated light (64742-47-8) | |
| Partition coefficient n-octanol/water (Log Pow) | 3.3 – 6 Source: IUCLID |
| Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) (577-11-7) | |
| Partition coefficient n-octanol/water (Log Pow) | 6.1 Source: ChemIDplus |
| White mineral oil (petroleum) (8042-47-5) | |
| Partition coefficient n-octanol/water (Log Pow) | 5.18 Source: Quantitative Structure Activity Relation |

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available




SECTION 13: Disposal considerations

13.1. Disposal methods

| | |
|--|--|
| Regional waste regulation | : Dispose of contents/container in accordance with local/regional/national regulations. Avoid release to the environment. |
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Sewage disposal recommendations | : Disposal must be done according to official regulations. Do not allow to enter sewers, surface or groundwater. |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations. Full or partially-full aerosol cans can be treated as universal waste. Empty container can be recycled. |
| Hazardous waste code | : This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal. |
| Additional information | : Contents under pressure. |

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

| DOT | IMDG | IATA |
|---|---|---|
| 14.1. UN number | | |
| UN1950 | 1950 | 1950 |
| 14.2. Proper Shipping Name | | |
| Aerosols (Limited quantity) | AEROSOLS (Limited quantity) | Aerosols, non-flammable (Limited quantity) |
| 14.3. Transport hazard class(es) | | |
| LTD QTY | LTD QTY | LTD QTY |
|  |  |  |
| 14.4. Packing group | | |
| Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | |
| No supplementary information available | | |

14.6. Special precautions for user

DOT

| | |
|---|---|
| Class (DOT) | : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115 |
| UN-No. (DOT) | : UN1950 |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 306 |

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Class (IMDG) : 2 - Gases
Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP200
Packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

IATA

Class (IATA) : 2 - Gases
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provision (IATA) : A98, A145, A167, A802
ERG code (IATA) : 2L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Toxic Substances Control Act (TSCA)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

| Name | CAS-No. | Commercial status | Flags |
|---------------------------------------|------------|-------------------|-------|
| Water | 7732-18-5 | Active | XU |
| Petroleum gases, liquefied, sweetened | 68476-86-8 | Active | |

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| | | | |
|--|------------|--------|----|
| Propane | 74-98-6 | Active | |
| Butane | 106-97-8 | Active | |
| Distillates (petroleum), hydrotreated light | 64742-47-8 | Active | |
| Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) | 577-11-7 | Active | |
| White mineral oil (petroleum) | 8042-47-5 | Active | |
| Sorbitan trioleate ; (Z,Z,Z)-Sorbitan tri-9-octadecanoate | 26266-58-0 | Active | |
| Polyoxyethylene sorbitan trioleate | 9005-70-3 | Active | XU |
| Polyoxyethylene dioleate | 9005-07-6 | Active | XU |

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substance

| | |
|---------------------------------|---|
| CERCLA Section 103 (40CFR302.4) | Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee. |
|---------------------------------|---|

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 302 Extremely Hazardous Substance

Not listed

Section 304 Emergency Release Notification

Not listed

Sections 311/312 Hazard Classification

Not listed

Section 313 (TRI Reporting)

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Additional Regulatory Information

This product is not compliant to be sold for use in New York, as it exceeds the 1,4 -dioxane limit in household cleaning products per New York's Environmental Conservation Law Articles 35 and 37.

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65



WARNING:

This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| U.S. - California - Proposition 65 - Carcinogens List | |
|---|--------|
| 1,4-Dioxane (123-91-1) | LISTED |
| Ethylene oxide (75-21-8) | LISTED |
| Diethanolamine (111-42-2) | LISTED |

| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | |
|---|--------|
| Ethylene oxide (75-21-8) | LISTED |

| U.S. - California - Proposition 65 - Reproductive Toxicity - Male | |
|---|--------|
| Ethylene oxide (75-21-8) | LISTED |

| U.S. - California - Proposition 65 - Developmental Toxicity | |
|---|--------|
| Ethylene oxide (75-21-8) | LISTED |

State Regulations

| Component | State Regulations |
|---|---|
| Propane(74-98-6) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Butane(106-97-8) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Distillates (petroleum), hydrotreated light(64742-47-8) | U.S. - Rhode Island - Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |
| White mineral oil (petroleum)(8042-47-5) | U.S. - Rhode Island - Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |

CRC® HydroForce® Stainless Steel Cleaner and Polish, 18 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

15.4 Other Regulatory Information

Volatile organic compound (VOC) regulation

EPA

| | |
|--|----------------|
| VOC content (40 CFR 51.100(s)) | 35.2 % |
| Consumer products (40 CFR 59, Subpt. C)) | Not regulated. |

State

| | |
|-------------------|---|
| Consumer products | This product is regulated as a Metal Polish or Cleanser (aerosol). This product is not compliant to be sold for use in New York. This product is compliant in all other states. |
| VOC Content (CA) | 14.5 % |
| VOC Content (OTC) | 14.5 % |

SECTION 16: Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| | |
|-------------------|-----------------------|
| Author | : Angelina Cibulskis |
| Other information | : CRC # 925B/1002931. |

Safety Data Sheet (SDS), USA, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Inc.